



STANDARD FLOW
BUSHING ON OUTLET SIDE

TRIM DIAMETER		HUB SIZE	NUMBER OF BLADES	BUSHING TYPE	MAXIMUM SHAFT SIZE	DIMENSIONS				
MIN	MAX					A	B	C	D	E
11.5	38.0	150	5 or 10	H	1 3/8	5.9	1.1	1.0	1.5	1.4
22.0	42.0	250	7 or 14	P1	1 5/8	9.8	1.2	1.0	1.5	1.9
24.0	51.0	255	2,3,4,6	P1	1 3/4	10.0	1.3	1.6	2.4	2.1
27.0	55.0	350	3,4,6,12	Q1	2 11/16	13.8	1.9	1.6	2.4	2.1
39.0	72.8	400	3,6,9	Q2	2 5/8	15.8	2.1	2.2	3.4	3.5
39.0	78.7	550	3,4,6,12	R2	3 5/8	21.7	2.6	2.2	3.4	3.5

"C" DIMENSION OF LEADING EDGE AT MAXIMUM BLADE PITCH
"D" DIMENSION OF TRAILING EDGE AT MAXIMUM BLADE PITCH

TRIM DIAMETER

REVERSE FLOW
BUSHING ON INLET SIDE

		CFM	
		Better Airflow By Design	
		TITLE PROPPELLER DIMENSIONS	
		ADJUSTABLE PITCH SUBMITTAL	
REV	DATE	BY	BY J. E. EVANS DATE 16 DEC. 2002 CFM LITERATURE.dft